

Sealed distribution box. 11 modules. IP54.

Sealed distribution box. 11 modules. IP54.IK07. White colour. External dimensions 230 x 180 x 86 mm. Smooth laterals. Sealable. 1/4 turn closure screw.



Features

Enclosure type	Sealable layout
Installation method	Surface
Use	Domestic / Tertiary
Location type	Exterior and interior
No. Modules (18 mm)	11
Modules per row	11
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	230x180x86
Dimensions inside (mm) (Width x Height x Depth)	220x170x80
Case material	Insulation
Frame and door material	Insulation
Case color	White
Door color	White
Door opening	Horizontal
Battens included	No
Ticket type	Smooth sides (machining inlets)
Fixation System (For surface)	Inside with plug (To ensure class II and IP)
Sealable	Yes
Lid closure system	1/4 turn screw with spring
Door closing system	Handle

Possibility of mounting strips	Yes (not included)
Separate covers or doors on the boxes	Yes
Possibility of mounting DIN rail	Yes (included)
Valid for photovoltaic installations	Yes
Common applications	Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)

Technical data

Protection Degree (IK)	IK07
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Work stress	400 Vac
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sketch

