

Sealed polyester cabinet. Plain door (opaque). Empty, dimensions 300x400x200

Sealed polyester cabinet. Plain door (opaque). Empty, dimensions 300x400x200



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	300x400x200
Case material	Polyester
Frame and door material	Polyester
Case color	Grey (RAL7035)
Cap color	Grey
Door color	Grey (RAL7035)
Door opening	Horizontal
Battens included	No
Ticket type	Smooth sides (machining inlets)
Fixation System (For surface)	Exterior with support
Sealable	Yes
Door closing system	Triangle closure
Possibility of mounting strips	Yes (not included)
Possibility of putting lock	Key
Possibility of mounting plate	Yes (not included)

Possibility of mounting DIN rail	Yes (not included)
Valid for photovoltaic installations	Yes
Common applications	Industrial environments (factories, warehouses, etc.)

Technical data

Protection Degree (IP)	IP66
Protection Degree (IK)	IK10
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	960 °C
Heat resistance (Ball pressure)	125 °C
Installation temperature	-15 °C -> +60 °C
Work stress	<1000 Vac ; 1500 Vdc
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes