

Residual Current Circuit-Breaker 2P, 40A. AC curve.
Sensitivity 30 mA

Residual Current Circuit-Breaker 2P, 40A. AC curve. Sensitivity 30 mA2 modules.
240/415V AC (50 - 60 Hz). Breaking capacity 6kA.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanical durability	15.000 cycles
Protection type (modular)	Diferential switch
No. of poles	1P + N
Modules (18 mm)	2
Neutral position	Left
Network type	Alternating current (ac)
Sensitivity (Leakage current)	30 mA
Short circuit capacity	6 kA
Protection type	Class AC
Delay type	Instant (No delay)
Fixation	35mm DIN rail
Connection capacity	Up to 35 mm²
Possibility of using pin type combs	Yes
Nominal current	40A
Nominal voltage	230 Vca - (50/60 Hz)

Technical data

Fire resistance (GWT)	960°C
Ambient operating temperature	-5°C -> +40°C

Free of halogens	Yes
------------------	-----

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE EN 61008-1
According to REBT	Yes
AENOR certificate	Yes
CB certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes