

Industrial distribution box of 22 modules.

Industrial distribution box of 22 modules.2 rows. IP65. IK08. External dimensions 270 x 500 x 160 mm. Lateral, upper and lower pre-cut. Stainless steel ultra fast closing screws.
Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
No. Modules (18 mm)	22
Modules per row	11
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	270x500x160
Case material	Insulation
Case color	Gray (RAL7035)
Cap color	Gray (RAL 7035)
Door color	Blue
Door opening	Vertical
Battens included	No
Ticket type	Pre-punched
No. of inlets and size (mm)	SUP/INF: 4xØ20, 4xØ25, 6xØ40. LAT: 8xØ40
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw

Door closing system	Handle
Possibility of mounting strips	Yes (not included)
Possibility of mounting with key / padlock	Lock and key
Possibility of mounting DIN rail	Yes (included)
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70°C
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes