

Sealed connection box Ø 70 x 35 mm with cones.
Grey colour

Sealed connection box Ø 70 x 35 mm with cones. Grey colour.IP55. IK07. Snap cover. With 4 cones for tube Ø 20 mm. With 4 holes for M20 cable glands. Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Domestic / Tertiary
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	Ø 77x40
Dimensions inside (mm) (Width x Height x Depth)	Ø 70x35
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Ticket type	With cones
No. of inlets and size (mm)	4x Ø20
Fixation System (For surface)	Exterior
Lid closure system	A Pressure
Possibility of mounting strips	Yes (not included)
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP55
Protection Degree (IK)	IK07

Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	<1000 Vac ; 1500 Vdc
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sketch



