

Surface distribution board, 56 modules.

Surface distribution board, 56 modules.4 rows. White colour. Surface distribution box up to 56 modules. External dimensions 362 x 686 x 104 mm. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Distribution
Installation method	Surface
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	56
Modules per row	14
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	362x686x104
Case material	Insulation
Frame and door material	Insulation
Case color	White
Cap color	White
Door color	White
Door opening	Horizontal
Battens included	No
Ticket type	Pre-punched
Fixation System (For surface)	Inside
Sealable	Not
Lid closure system	Metal screw

Door closing system	A Pressure
Reversible door	Yes
Possibility of mounting strips	Yes (not included)
Possibility of putting lock	Key
Separate covers or doors on the boxes	Yes
Possibility of mounting DIN rail	Yes (included)

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK08
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	<1000 Vca ; 1500 Vcc
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Sketch

