

Flush connection box in hollow partition. Ø 100 mm. Square leveling cover. Perimeter adjustment. With central screw.

Flush connection box in hollow partition. Ø 100 mm. Square leveling cover. Perimeter adjustment. With central screw. Depth 46 mm. 10 inputs for tube Ø 25 and 4 inputs for tube Ø 104 mm. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Connection and derivation
Installation method	For dry wall
Use	Domestic / Tertiary
Location type	Inside
Dimensions inside (mm) (Width x Height x Depth)	Ø 100x46
Case material	Insulation
Case color	Blue
Cap color	White
Ticket type	Unfathomable
No. of inlets and size (mm)	10xØ25
Lid closure system	Perimeter adjustment + screw
Fixing system to the hollow partition.	Metal claw
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes

Technical data

Fire resistance (GWT)	850°C
-----------------------	-------

Heat resistance (Ball pressure)	70°C
Ambient operating temperature	-5°C ->+60°C
Work stress	400 Vca
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1; -22
According to REBT	Yes
AENOR certificate	Yes
CB certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Not applicable
According to European Directive 2012/19/UE (RAEE2)	Not applicable
ECOEMBES	Yes