

Flush efficient mechanism box in hollow partition.
For 2 modules. Nylon ties fixing system.

Flush efficient mechanism box in hollow partition. For 2 modules. Nylon ties fixing system. Flush dimensions 139 x 68 mm. 4 inputs for tube Ø 16-20 mm. 2 inputs for tube Ø 20-25 mm. Use cutter Ø 68 mm.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Mechanism box
Installation method	For dry wall
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	2
Dimensions gap (mm) (Width x Height x Depth)	139X68X46 mm
Case material	Insulation
Case color	Blue
Ticket type	Flexible membrane
No. of inlets and size (mm)	2 entradas para tubo Ø 16-20 y 4 entradas para tubo Ø 20-25
Alignment marks	Alignment Marks
Fixing system to the hollow partition.	Nylon flange

Technical data

Fire resistance (GWT)	850°C
Installation temperature	-5°C -> +60°C
Ambient operating temperature	-5°C ; +60°C
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).
According to European Directive 2001/95 / CE. General Product Safety Directive	Yes