

Multiple socket of 4 sockets 2P+E, 16A 250V~. With light switch.

Multiple socket of 4 sockets 2P+E, 16A 250V~. With light switch.MAX. 3680W. 850° C GWT Graphite colour. Easy cable connection. Inputs for 7 x 12, 10 x 16, 10 x 20 and 12 x 12 mm mini-trunking. Quick and easy removal lid. With holes for fixing by screws to the wall and orifice for fixing by means of flanges to tubes. Includes rubber grommet for cable and cover for mini trunking. Made of Polycarbonate. Serie ION. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	4
Basic characteristics	2P+E, 16A 250V~
Maximum power	3.680 W
Light switch	Yes
Terminal system	Screw connection
Mini trunking input	Yes, for 7x12, 10x16, 10x20 and 12x12
Possibility of using hanger	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C
Ambient operating temperature	-5 °C ; +60 °C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

According to Regulations UNE/EN	UNE-20315-1-1:2017; UNE-20315-1-2:2017
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sketch

