

Multiple socket of 5 sockets 2P+E, 16A 250V~. With light switch.

Multiple socket of 5 sockets 2P+E, 16A 250V~. With light switch. MAX. 3680W. White colour. Easy connection access. With fixing holes to the wall. Inputs for 7x12, 10x16, 10x20 and 12x12 mm mini-trunking. Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	5
Basic characteristics	2P+T, 16A 250V~
Cable length	1,5 m.
Maximum power	3.680 W
Light switch	Yes
Cable	Yes
Cable Features	H05VV-F 3G1,5mm²
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	125°C
Ambient operating temperature	-5°C ->+60°C

Regulations

CE marking	Yes
------------	-----

CMim marking	Yes
According to Regulations UNE/EN	UNE 20315-1-1; -1-2
According to REBT	Yes
Intertek GS certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes
ECOEMBES	Yes