

Multiple socket of 6 sockets 2P+E, 16A 250V~.

Multiple socket of 6 sockets 2P+E, 16A 250V~.MAX. 3680W. White colour. Easy access emborning. With fixing holes to the wall. Inputs for 7x12, 10x16, 10x20 and 12x12 mm mini-trunking.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	6
Basic characteristics	2P+T, 16A 250V~
Maximum power	3.680 W
Terminal system	Screw connection
Mini trunking input	H05VV-F 2x1mm²
Possibility of using hanger	Yes
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	125°C
Ambient operating temperature	-5°C ->+60°C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE 20315-1-1; -1-2
According to REBT	Yes
Intertek certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes
ECOEMBES	Yes