

Flush distribution board, 2 modules.

Flush distribution board, 2 modules.White frame and door. Flush dimensions 60 x 130 x 62 mm.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Distribution
Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	2
Modules per row	2
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	62x140x85
Dimensions inside (mm) (Width x Height x Depth)	60x130x62
Case material	Insulation
Frame and door material	Insulation
Case color	Black
Cap color	White
Door color	White
Door opening	Vertical
Battens included	No
Ticket type	Unfathomable
Fixation System (For surface)	Inside

Sealable	Not
Lid closure system	Metal screw
Door closing system	A Pressure
Reversible door	Yes
Possibility of putting lock	Not
Separate covers or doors on the boxes	Yes
Possibility of mounting DIN rail	Yes (included)

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK08
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
Installation temperature	-5 °C -> +60 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	<1000 Vca ; 1500 Vcc
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
---	--

According to European Directive
2012/19/UE (RAEE2)

Not applicable because it does not meet the definition of Electrical and Electronic
Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).

Sketch

