

Luminaire junction box 87 x 78 x 38 mm. IP68. With 3P terminal for cable 0,5-2,5 mm².

Luminaire junction box 87 x 78 x 38 mm. IP68. With 3P terminal for cable 0,5-2,5 mm². Black colour. 24A 250V, T60, GWT 750°C. PC material. 3 M25 cable glands, cables Ø 4-8 mm + 3 adapters 8-12mm + 3 adapters 10-14 mm + 1 cap. Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Domestic / Tertiary
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	93x73x38
Dimensions inside (mm) (Width x Height x Depth)	70x57x30
Cable section	6mm2
Case material	Insulation
Case color	Black
Cap color	Black
Ticket type	With cable glands
No. of inlets and size (mm)	3
Fixation System (For surface)	Exterior
Sealable	Yes
Lid closure system	Metal screw
Possibility of mounting strips	Yes (included)
Drain type	Deflowable Drainage

Technical data

Protection Degree (IP)	IP68
Protection Degree (IK)	IK07
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70/125°C
Ambient operating temperature	-5°C ->+60°C
Work stress	<1000 Vca ; 1500 Vcc
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-22
According to REBT	Yes
KEMA EUR certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Not applicable