

Derivation T connector watertight 3P. IP68.

Derivation T connector watertight 3P. IP68: depth 4 m. For permanent installation. 1 output (3G4) and 2 outputs (3G2,5). Dimensions: Ø33x115x100 mm. With 3 cable glands for Ø 4-8 mm cable, 3 interchangeable rubber gaskets for Ø 9-12 mm cable and 3 for Ø 10-14 mm cable. Stripped: Cable (7-8mm) - Cover (18-20mm).

Common applications: Industrial environments (factories, warehouses, etc.)



Features

Number of terminals	3 x 4 mm²
Flexible cable minimum section	0,5 mm²
Flexible cable maximum section	4 mm²
Diameter (mm)	4 a 14 mm
Color	Black

Technical data

Protection Degree (IP)	IP68
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	125°C
Ambient operating temperature	-40°C -> +85°C
Work stress	400 Vca
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE-EN 60998-1 UNE-EN 60998-2-1
According to REBT	Yes
TÜV Rheinland certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes