

Flush distribution box in hollow partition of 14 modules. Fixing system using metal claws. Ref. G-MP28.

Flush distribution box in hollow partition of 14 modules. Fixing system using metal claws. Ref. G-MP28. With white metal frame and door. Blue box and white cover thermoplastic material. External dimensions 362 x 327 x 88 mm. 30W thermal dissipation.



Features

Enclosure type	Distribution
Installation method	For hollow wall.
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	14
Modules per row	14
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	362x327x88
Dimensions gap (mm) (Width x Height x Depth)	333x300x88
Case material	Composite
Frame and door material	Metallic stainless
Case color	Blue
Cap color	White
Door color	White
Door opening	Horizontal
Battens included	Yes (Screw terminals)
Strip type	Ground
No. of terminals and size	13x6 mm2 + 4x16 mm2
Ticket type	Unfathomable

Linkable	Vertically and horizontally
Lid closure system	1/4 turn screw without spring
Door closing system	Handle
Reversible door	Yes
Possibility of mounting strips	Yes (included)
Possibility of putting lock	Key
Possibility of mounting DIN rail	Yes (included)
Possibility of mounting .PL-MP28 plate	Yes (not included)
Fixing system to the hollow partition.	Metal claw
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes
With recessed hole marking system	Yes
Common applications	Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK07
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	70 °C
Ambient operating temperature	-5 °C ; +60 °C
Work stress	<1000 Vac ; 1500 Vdc
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208:2012
According to REBT	Yes

According to European Directive 2014/35 / Yes
EU. Low voltage directive

Sketch

