

Flush distribution box in hollow partition of 42 modules. Fixing system using metal claws. Ref. G-MP28.

Flush distribution box in hollow partition of 42 modules. Fixing system using metal claws. Ref. G-MP28.3 rows. With white metal frame and door. Blue box and white cover thermoplastic material. External dimensions 362 x 643 x 88 mm. 35W thermal dissipation.



Features

|                                                  |                       |
|--------------------------------------------------|-----------------------|
| Enclosure type                                   | Distribution          |
| Installation method                              | For hollow wall.      |
| Use                                              | Domestic / Tertiary   |
| Location type                                    | Inside                |
| No. Modules (18 mm)                              | 42                    |
| Modules per row                                  | 14                    |
| Removable frame                                  | Yes                   |
| Metallic DIN profile                             | Yes                   |
| Dimensions outside (mm) (width x height x depth) | 362X643X88            |
| Dimensions gap (mm) (Width x Height x Depth)     | 333x620x88            |
| Case material                                    | Composite             |
| Frame and door material                          | Metallic stainless    |
| Case color                                       | Blue                  |
| Cap color                                        | White                 |
| Door color                                       | White                 |
| Door opening                                     | Horizontal            |
| Battens included                                 | Yes (Screw terminals) |

|                                                                                  |                                                                                 |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------|
| Strip type                                                                       | Ground                                                                          |
| No. of terminals and size                                                        | 18x6 mm2 + 6x16 mm2                                                             |
| Ticket type                                                                      | Unfathomable                                                                    |
| Linkable                                                                         | Vertically and horizontally                                                     |
| Lid closure system                                                               | 1/4 turn screw without spring                                                   |
| Door closing system                                                              | Handle                                                                          |
| Reversible door                                                                  | Yes                                                                             |
| Possibility of mounting strips                                                   | Yes (not included)                                                              |
| Possibility of putting lock                                                      | Key                                                                             |
| Possibility of mounting DIN rail                                                 | Yes (included)                                                                  |
| Possibility of mounting .PL-MP28 plate                                           | Yes (not included)                                                              |
| Fixing system to the hollow partition.                                           | Metal claw                                                                      |
| With grommets at the bottom to fix the tubes or cables with cable ties, quantity | Yes                                                                             |
| With recessed hole marking system                                                | Yes                                                                             |
| Common applications                                                              | Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.) |

## Technical data

|                                 |                      |
|---------------------------------|----------------------|
| Protection Degree (IP)          | IP40                 |
| Protection Degree (IK)          | IK07                 |
| Impact shock resistance         | Medium               |
| Insulation class                | Class II             |
| Fire resistance (GWEPT)         | 850 °C               |
| Heat resistance (Ball pressure) | 70 °C                |
| Ambient operating temperature   | -5 °C ; +60 °C       |
| Work stress                     | <1000 Vac ; 1500 Vdc |
| Free of halogens                | Yes                  |

## Regulations

|              |     |
|--------------|-----|
| CE marking   | Yes |
| UK marking   | Yes |
| CMim marking | Yes |

|                                                                        |                   |
|------------------------------------------------------------------------|-------------------|
| According to Regulations UNE/EN                                        | UNE-EN 62208:2012 |
| According to REBT                                                      | Yes               |
| According to European Directive 2014/35 /<br>EU. Low voltage directive | Yes               |

Sketch

