

Socket 2P+E, 16A 250V ~ + USB socket 2.1A 5V.

Socket 2P+E, 16A 250V ~ + USB socket 2.1A 5V. Flush. White colour. Dimensions 83 x 81 mm. With shutter. Quick connection.
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	Fixed base + USB
Type of installation	Flush
Rated current	16A - 2,1Adc
Nominal voltage	250V~ (50/60 Hz) - 5Vdc
Connection type	Fast connection
Dimensions	83 x 81
With fixing claws	Yes
Monobloc (with frame included)	Yes
Key color	White
Frame color	White

Technical data

Protection Degree (IP)	IP40
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	70/125°C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes