

Sealed distribution box. 3 modules. IP54.

Sealed distribution box. 3 modules. IP54.IK07. White colour. External dimensions 82 x 155 x 82 mm. Smooth laterals. Sealable. Closure with metallic threaded screws. Without connection terminal.

Common applications: Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)



Features

Enclosure type	Sealable layout
Installation method	Surface
Use	Domestic / Tertiary
Location type	Exterior and interior
No. Modules (18 mm)	3
Modules per row	3
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	82x155x82
Dimensions inside (mm) (Width x Height x Depth)	75x145x75
Case material	Insulation
Frame and door material	Insulation
Case color	White
Door color	White
Door opening	Horizontal
Battens included	No
Ticket type	Smooth sides (machining inlets)
Fixation System (For surface)	Inside
Sealable	Yes
Lid closure system	Metal screw

Door closing system	Handle
Separate covers or doors on the boxes	Yes
Possibility of mounting DIN rail	Yes (included)
Drain type	Deflowable Drainage
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP54
Protection Degree (IK)	IK07
Impact shock resistance	Medium
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70°C
Installation temperature	-5°C -> +60°C
Work stress	400 Vca
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2012/19/UE (RAEE2)	Yes
--	-----

Logistics and packaging

EAN code container	8423220229891
Units Container	1
Units Packaging	72
Pallet Units	1.080
Packaging Measures cm	58,3 x 38,5 x 46,5
Unit weight (Kg)	269
Container Weight (Kg)	0,28
Packaging Weight (Kg)	21,03
Tariff code	85371098