

Sealed polyester cabinet. Transparent door. Empty, dimensions 400x500x200

Sealed polyester cabinet. Transparent door. Empty, dimensions 400x500x200
Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	400x500x200
Case material	Polyester
Frame and door material	Polyester
Case color	Gray (RAL7035)
Cap color	Transparent
Door color	Transparent
Door opening	Horizontal
Battens included	No
Ticket type	Smooth sides (machining inlets)
Fixation System (For surface)	Exterior with support
Sealable	Inside with plug, outside with bracket or flange.
Door closing system	Triangle closure
Possibility of mounting strips	Yes (not included)
Possibility of mounting with key / padlock	Key
Possibility of mounting plate	Yes (not included)

Possibility of mounting DIN rail	Yes (not included)
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP66
Protection Degree (IK)	IK10
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWT)	960°C
Heat resistance (Ball pressure)	125°C
Installation temperature	-15°C -> +60°C
Work stress	<1000 Vca ; 1500 Vcc
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Not applicable
According to European Directive 2012/19/UE (RAEE2)	Not applicable

Logistics and packaging

EAN code container	8423220216280
Units Container	1
Units Packaging	1
Pallet Units	0
Tariff code	85371098