

Industrial distribution box of 8 modules. Cover with 3 openings for industrial flush sockets.

Industrial distribution box of 8 modules. Cover with 3 openings for industrial flush sockets.IP65. IK08. External dimensions 215 x 500 x 160 mm. Lateral, upper and lower pre-cut. Stainless steel ultra fast closing screws. Linkable
Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
No. Modules (18 mm)	8
Modules per row	8
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	215x500x160
Case material	Insulation
Case color	Gray (RAL7035)
Cap color	Gray (RAL 7035)
Battens included	No
Ticket type	Pre-punched
No. of inlets and size (mm)	SUP/INF: 4xØ20, 4xØ25, 6xØ40. LAT: 8xØ40
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Door closing system	Handle
Possibility of mounting strips	Yes (not included)

Possibility of mounting with key / padlock	Lock and key
Possibility of mounting DIN rail	Yes (included)
Valid for photovoltaic installations	Yes
Windows for industrial sockets	3 panel-fitted socket

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70°C
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes