

Sealed connection box without cones. Grey colour.
Cover with 9 openings for flush industrial socket.

Sealed connection box without cones. Grey colour. Cover with 9 openings for flush industrial socket. Grey colour. Internal dimensions 355 x 493 x 129 mm. Quick closure with stainless screws. Pre-cut lateral. Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	362x500x140
Dimensions inside (mm) (Width x Height x Depth)	355x493x129
Case material	Insulation
Case color	Gray (RAL7035)
Cap color	Gray (RAL 7035)
Battens included	No
Ticket type	Pre-punched
No. of inlets and size (mm)	SUP/INF: 4xØ20, 4xØ25, 6xØ40. LAT: 8xØ40
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Possibility of mounting strips	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (not included)
Valid for photovoltaic installations	Yes

valid for photovoltaic installations	yes
Windows for industrial sockets	9 panel-fitted socket

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70°C
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
APPlus certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes